

GY 701TL

MOTOAZADA GASOLINA
PETROL TILLER



Ref.: GY701TL

ESPECIFICACIONES TÉCNICAS TECHNICAL SPECIFICATIONS

| | | | GY 701TL |
|------------------------------|---|------------------------------------|---|
| MOTOR ENGINE | Marca | Brand | GOODYEAR Licensed |
| | Modelo | Model | OHV (4T) |
| | Cilindrada (cm ³) | Displacement (cm ³) | 212 |
| | Potencia Máxima (Kw / hp) | Max. Power (Kw / hp) | 5,25 / 7,0 (3600 rpm) |
| | Potencia Nominal (Kw / hp) | Rated Power (Kw / hp) | 4.4 / 6 (3600 rpm) |
| | Diametro x Carrera (mm) | Bore x stroke(mm) | 70x55 |
| | Torque Max. | Max. Torque | 12,0 Nm / 2800rpm |
| | Capacidad tanque combustible | Fuel tank capacity | 4L |
| | Capacidad tanque aceite | Oil tank capacity | 0.6L |
| | Filtro aire | Air Filter | Oil bath |
| | Dimensiones de la máquina (mm) | Body sizes (mm) | 1380 x 650 x 970 |
| Dimensiones de motor (mm) | Engine Measures (mm) | 400 x 375 x 380 | |
| CONSTRUCCIÓN CONSTRUCTION | Transmision | Transmission | Cadena en baño de aceite / Chain Oil Bath |
| | Embrague | Clutch | Double belt |
| | Velocidades | Gears | -1,0,2,1 |
| | Ancho de trabajo | Working width | 500-600-800 mm |
| | Manillar | Bike handle | Regulable en altura / Height regulation |
| | Cuchillas | Blades | 24 |
| | Profundidad de trabajo | Working Depth | 150-300 mm |
| Seguridad | Security | Parada automatica / Automatic stop | |
| EMBALAJE PACKING | Incluye (Accesorios) | Included (Accessories) | Rueda 400-8mm - Rueda delantera - Grupo de 3 cuchillas - Discos redondos - Aporcador fijo/ Wheels 400-8mm - Front wheel - 3 groups blades - Round discs - Fix Ridger |
| | Dimensiones (mm) | Dimensions (mm) | 820 x 450 x 780 |
| | Peso Neto | Net weight | 67 Kg |
| | Peso Bruto | Gross weight | 78 Kg |
| | Capacidad contenedor (20' / 40' / 40HQ) | Container loads (20' / 40' / 40HQ) | 105/210/210 |
| Código EAN | EAN Code | 8434691360822 | |

